

SAFETY DATA SHEET

New Zealand HSNO Compliant

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name RAMSET LUBRICATING AND RELEASE OIL

Synonyms LUBRICATING AND RELEASE OIL ● PA9316 - PRODUCT CODE

1.2 Uses and uses advised against

Uses LUBRICANT ● RELEASE AGENT

1.3 Details of the supplier of the product

Supplier name RAMSETREID NZ (A DIVISION OF ITW NEW ZEALAND)

Address 23-29 Poland Road, Glenfield, Auckland, 0627, NEW ZEALAND

Telephone 0800 88 22 12

Emailsales@ramsetreid.co.nzWebsitehttp://www.reids.co.nz

1.4 Emergency telephone numbers
Emergency 0800 734 607

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

HAZARDOUS ACCORDING TO NZ ENVIRONMENTAL PROTECTION AUTHORITY CRITERIA

Physical Hazards

2.1.2A - Flammable aerosols: Category 1 Aerosols - Pressurised: Category 1

Health Hazards

Not classified as a Health Hazard

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

Prevention statements

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

ChemAlert.

SDS Date: 04 May 2021

PRODUCT NAME RAMSET LUBRICATING AND RELEASE OIL

Response statements

None allocated.

Storage statements

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Disposal statements

None allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	232-455-8	>60%
PETROLEUM GASES, LIQUEFIED (<0.1% W/W 1,3-BUTADIENE)	68476-85-7	270-704-2	10 to 30%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or

an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact the National Poisons Centre on 0800 764 766 (0800 POISON) or +643 479 7248 or a

doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

First aid facilities Eye wash facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters, pilot lights, mobile phones, etc when handling. Aerosol cans may explode above 50°C.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

2YE

2 Fine Water Spray.

Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

E Evacuation of people in and around the immediate vicinity of the incident should be considered.



SDS Date: 04 May 2021 Revision No: 3

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/leaking containers. Large storage areas should have appropriate fire protection systems.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
	Kelefelice	ppm	mg/m³	ppm	mg/m³
LPG (Liquefied petroleum gas)	WES [NZ]	1000	1800		
Mineral Oil Mist	WES [NZ]		5		

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face Wear splash-proof goggles. **Hands** Wear PVC or rubber gloves.

Body When using large quantities or where heavy contamination is likely, wear coveralls.

Respiratory At high vapour levels, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator.







SDS Date: 04 May 2021 Revision No: 3

Page 3 of 7

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance CLEAR LIQUID (AEROSOL DISPENSED)

Odour SLIGHT ODOUR

Flammability EXTREMELY FLAMMABLE

Flash point -30°C

Boiling point NOT AVAILABLE
Melting point NOT AVAILABLE
Evaporation rate NOT AVAILABLE
pH NOT AVAILABLE
Vapour density NOT AVAILABLE

Relative density 0.85
Solubility (water) INSOLUBLE
Vapour pressure 379 kPa
Upper explosion limit 7.5 %
Lower explosion limit 1.2 %

Partition coefficient
Autoignition temperature
Decomposition temperature
Viscosity
Explosive properties
Oxidising properties
Odour threshold
NOT AVAILABLE
NOT AVAILABLE
NOT AVAILABLE
NOT AVAILABLE
NOT AVAILABLE

9.2 Other information

% Volatiles 90 % (Approximately)

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. This product may have the potential to cause

adverse health effects if intentionally misused (e.g. deliberately inhaling contents).

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
WHITE MINERAL OIL (PETROLEUM)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)	5 mg/L/4hrs (rat)

Skin Not classified as an irritant. Contact may result in mild irritation, drying and defatting of the skin, rash and

dermatitis

Eye Not classified as an eye irritant. Contact may cause discomfort, lacrimation and redness.



SDS Date: 04 May 2021 Revision No: 3

PRODUCT NAME RAMSET LUBRICATING AND RELEASE OIL

Sensitisation Not classified as causing skin or respiratory sensitisation.

Mutagenicity Not classified as a mutagen. Carcinogenicity Not classified as a carcinogen.

Reproductive Not classified as a reproductive toxin.

STOT - single Not classified as causing organ damage from single exposure. However, over exposure may result in mild irritation of the nose and throat, with coughing. High level exposure may result in dizziness, nausea and exposure

headache.

STOT - repeated

exposure

Not classified as causing organ damage from repeated exposure.

Aspiration Ingestion is considered unlikely due to product form.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of in accordance with advice from the Environmental Protection Authority. Waste disposal

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD ACCORDING TO LAND TRANSPORT RULE: DANGEROUS GOODS 2005; NZS 5433:2012, UN, IMDG OR IATA



	LAND TRANSPORT (NZS 5433)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1950	1950	1950
14.2 Proper Shipping Name	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packing Group	None allocated.	None allocated.	None allocated.

Page 5 of 7

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code 2YE **EmS** F-D, S-U

ChemAlert.

SDS Date: 04 May 2021

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Approval code HSR002515

Group standard Aerosols (Flammable) Group Standard 2006

Inventory listings AUSTRALIA: AllC (Australian Inventory of Industrial Chemicals)

All components are listed on AIIC, or are exempt.

16. OTHER INFORMATION

Additional information

AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists
---------------	-------	---

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CCID Chemical Classification and Information Database (HSNO)

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

EPA Environmental Protection Authority [New Zealand]

GHS Globally Harmonized System

HSNO Hazardous Substances and New Organisms IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value
TWA Time Weighted Average



SDS Date: 04 May 2021

PRODUCT NAME RAMSET LUBRICATING AND RELEASE OIL

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711

Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmtglobal.com

[End of SDS]



SDS Date: 04 May 2021