

OrbiPlateTM Bolted Connections

Product Identifier ORB2020BGH

Product description

The patented OrbiPlate[™] system delivers connection tolerances of up to 20mm in structural connections. OrbiPlate[™] is quick and easy to install delivering fine locational accuracy when positioning steel members.

Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (b, d, e, f, g, h, j, q), B1.3.4 B2 Durability — B2.3.1 (a)

Contributions to compliance

For B1 Structure refer to the OrbiPlate[™] Design Guide ANZ and the OrbiPlate TDS/FTA listed in supporting documentation. For B2 Durability all OrbiPlate[™] components are Hot Dip Galvanised in accordance with AS/NZS 4680:2006.

Scope of use

The patented OrbiPlate[™] system delivers connection tolerances of up to 20mm in structural connections. OrbiPlate[™] is quick and easy to install delivering fine locational accuracy when positioning steel members.

Conditions of use

OrbiPlate[™] should only be installed by a skilled professional after consultation with the specifier. OrbiPlate[™] requires installation in accordance with the OrbiPlate[™] Design Guide ANZ. OrbiPlate[™] models should only be installed in conjunction with the specific corresponding ferrule, laid out in the OrbiPlate[™] Design Guide ANZ.

Supporting documentation The following additional documentation supports the above statements:

| Title (type) | Version | URL |
|--|--------------|---|
| OrbiPlate™ TDS (Design, Installation, Test results) | FTA- 22/0006 | https://cdn.ramset.com.au/wp-content/uploads/2023/07/ramset_ORB- 2016BGH_ORB2020BGH_TDS_OrbiPlate%E2%84%A2-1.pdf |
| OrbiPlate™ Design Guide ANZ (Design, Installation, Maintenance) | July 2023 | https://cdn.ramset.com.au/wp-content/uploads/2023/07/ramset- ORB2020BGH-DesignGuide-ANZ-OrbiPlate-2.pdf |

| Contact details | |
|---|--|
| Manufacture location | Overseas |
| Legal and trading name of manufacturer | ITW CP SEA* |
| Legal and trading name of importer | Ramset [™] New Zealand |
| Importer address for service | 29 Poland Road, Auckland, 0627, New Zealand |
| Importer website | ramset.co.nz |
| Importer email | info@ramset.co.nz |
| Importer phone number | 0800 726 738 |
| Importer NZBN | 9429039833129 |
| *on the basis that ITW CP SEA partakes in the process packaging and supplying the product in New Zealand. | of manufacture, involving design, quality/safety testing, importing, |

Warnings and bans

This product line is not subject to any warning or ban under Section 26 of the Building Act 2004



OrbiPlateTM Bolted Connections

Appendix - Building code performance clauses

All relevant building code performance clauses listed in this document:

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during construction or alteration and throughout their lives.

B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during construction or alteration when the building is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of buildings, building elements and sitework,

including:

(b) imposed gravity loads arising from use

(d) earth pressure

(e) water and other liquids

(f) earthquake

(g) snow

(h) wind

(j) impact

(q) time dependent effects including creep and shrinkage

B1.3.4

Due allowances shall be made for:

a. the consequences of failure,

b. the intended use of the building,

c. effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,

d. variation in the properties of materials and the characteristics of the site, and

e. accuracy limitations inherent in the methods used to predict the stability of buildings

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the

lesser of the specified intended life of the building, if stated, or:

(a) the life of the building, being not less than 50 years, if:

i. those building elements (including floors, walls, and fixings) provide structural stability to the building, or

ii. those building elements are difficult to access or replace, or

iii. failure of those building elements to comply with the building code would go undetected during both normal use and

maintenance of the building

For further information, please contact Ramset"

NZ - PHONE: 0800 RAMSET (726738) www.ramset.co.nz

AU - PHONE: 1300 780 063 www.ramset.com.au

Ramset™ 1 Ramset Drive, Chirnside Park, Victoria. 3116. Australia © Copyright Sept 2023. ITW Australia Pty. Ltd. ABN 63 004 235 063 trading as Ramset™

Important Disclaimer: Any engineering information or advice ("Information") provided by Ramset[™] in this document is issued in accordance with a prescribed standard, published performance data or design software. It is the responsibility of the user to obtain its own independent engineering (or other) advice to assess the suitability of the Information for its own requirements. To the extent permitted by law, Ramset[™] will not be liable to the recipient or any third party for any direct or indirect loss or liability arising out of, or in connection with, the Information.