

TruBolt[™] Xtrem[™] Heavy Duty Anchors

Product Identifier Trubolt Xtrem T____X

Product description

The TruBolt™ Xtrem™ Anchor is a seismic certified heavy duty, torque-controlled expansion anchor for permanent anchoring in a wide range of structural and non-structural applications in concrete.

Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (a, b, c, d, e, g, h, l, j, p, q), B1.3.4

B2 Durability - B2.3.1 (a)

Contributions to compliance

For B1 Structure and B2 Durability refer to the TruBolt™ Xtrem™ European Technical Assessment ETA-21-0973 listed in supporting documentation.

Scope of use

The TruBolt[™] Xtrem[™] Anchor is a seismic certified heavy duty, torque controlled expansion anchor for permanent anchoring in a wide range of structural and non-structural applications in concrete. ETA Certified to Seismic C1 & C2 applications, meets SA TS101:2015 pre-qualification requirements.

Conditions of use

Installation of TruBolt[™] Xtrem[™] Anchors should be carried out by a competent professional, in accordance with the manufacturer's installation instructions found in the SARB.

Supporting documentation The following additional documentation supports the above statements:

Title (type)	Version	URL
TruBolt™ Xtrem™ SARB (Design, Installation)		https://ramset.co.nz/wp-content/uploads/2023/07/Ramset-SARB-ANZ-Ed.3-TruBolt-Xtrem- SEISMIC-MECHANICAL-ANCHORS.pdf
TruBolt™ Xtrem™ ETA (Certification, Test results)		https://ramset.com.au/wp-content/uploads/2023/07/TRUBOLT-XTREM_ZnSS.ETA_21_0973_ UK.pdf

Contact details	
Manufacture location	Overseas
Legal and trading name of manufacturer	ITW de France*
Legal and trading name of importer	Ramset™ New Zealand
Importer address for service	29 Poland Road, Auckland, 0627, New Zealand
Importer website	ramset.co.nz
Importer email	info@ramset.co.nz
Importer phone number	0800 726 738
Importer NZBN	9429039833129
*on the basis that ITW de France partakes in the process o importing, packaging and supplying the product in New Ze	

Warnings and bans

This product line is not subject to any warning or ban under Section 26 of the Building Act 2004



TruBolt™ Xtrem[™] Heavy Duty Anchors

Appendix - Building code performance clauses

All relevant building code performance clauses listed in this document:

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during construction or alteration and throughout their lives.

. B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during construction or alteration when the building is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of buildings, building elements and sitework,

including:

(a) self-weight

(b) imposed gravity loads arising from use

(c) temperature

(d) earth pressure

(e) water and other liquids

(f) earthquake

(g) snow

(h) wind

(i) fire

(j) impact

(p) equipment, services, non-structural elements and contents
(q) time dependent effects including creep and shrinkage

B1.3.4

- Due allowances shall be made for:
- a. the consequences of failure,
- b. the intended use of the building,

c. effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,

d. variation in the properties of materials and the characteristics of the site, and

e. accuracy limitations inherent in the methods used to predict the stability of buildings

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the

lesser of the specified intended life of the building, if stated, or:

(a) the life of the building, being not less than 50 years, if:

i. those building elements (including floors, walls, and fixings) provide structural stability to the building, or

ii. those building elements are difficult to access or replace, or

iii. failure of those building elements to comply with the building code would go undetected during both normal use and maintenance of the building

indiation of the ballang

For further information, please contact Ramset"

NZ - PHONE: 0800 RAMSET (726738) www.ramset.co.nz

AU - PHONE: 1300 780 063 www.ramset.com.au

Ramset™ 1 Ramset Drive, Chirnside Park, Victoria. 3116. Australia © Copyright Sept 2023. ITW Australia Pty. Ltd. ABN 63 004 235 063 trading as Ramset™

Important Disclaimer: Any engineering information or advice ("Information") provided by Ramset[™] in this document is issued in accordance with a prescribed standard, published performance data or design software. It is the responsibility of the user to obtain its own independent engineering (or other) advice to assess the suitability of the Information for its own requirements. To the extent permitted by law, Ramset[™] will not be liable to the recipient or any third party for any direct or indirect loss or liability arising out of, or in connection with, the Information.