

WallMate[™] Anchors

PERFORMANCE

MATERIAL

INSTALLATION RELATED











Description


The WallMate™ is the original self-drilling plasterboard anchor. Available in High Strength Nylon or Zinc, the WallMate™ is incredibly simple to use, requiring only a screwdriver to install, but also incredibly fast.

Features

- Both versions of the WallMate[™] feature an effective drill point for easy penetration of plasterboard and fast installation.
- If a long screw is used to secure the fixture, the anchor's drill point will break away so as not to restrict achievement of a firm fix.
- The anchor's screw thread profile is designed for efficient cutting and positive grip
- Both the screw and the WallMate[™] can be easily removed without losing the anchor inside the cavity, without damaging the plaster around the installation hole.
- The unique composition of Glass and Nylon increases the strength of the material, making this High Strength Nylon.




Installation



 Using a # 2 Phillips Head screwdriver with the WallMate[™] pierce through the plaster board.




Alternatively, a drill on low speed can be used to pierce through the plaster board stop before flush.



 Gently hand tighten the WallMate™ until the head sits flush with the surface.

Do not over tighten.



 Attach the desired Fixture up to a thickness of 15mm using a 6-8 Gauge screw.

| | PLASTERBOARD WALL THICKNESS SHEAR TENSION | | | | | | | | | | | |
|---|---|----------|-------------------|----------------|--|--|--|--|--|--|--|--|
| - | VV | 10mm | | | | | | | | | | |
| _ | | | 24Kg | 10Kg | | | | | | | | |
| _ | | 13mm | 33Kg | 15Kg | | | | | | | | |
| S | HEAR | TENSION | | | | | | | | | | |
| | | — | | | | | | | | | | |
| 1 | 10 | | DO NOT MOUNT TU/S | NON CONDUCTIVE | | | | | | | | |

Wallmates are not for overhead use, installing tv's or anchoring furniture (eg a chest of drawers) to walls

WEAR EYE PROTECTION



WallMate[™] Anchors

Description and Part Numbers

| Anchor | SKU | Description | Pack Qty | 10mm Plaster board | | 13mm Plasterboard | |
|----------|----------|-------------------------------|----------|--------------------|--------------|-------------------|--------------|
| AllClior | | | | SHEAR (kg) | TENSION (kg) | SHEAR (kg) | TENSION (kg) |
| | WM25/400 | WALLMATES NYLON BG400 | 400 | 24 | 10 | 33 | 15 |
| | WM6BK | WALLMATE NYLON BX250 | 250 | 24 | 10 | 33 | 15 |
| | WM25 | WALLMATE NYLON BX100 | 100 | 24 | 10 | 33 | 15 |
| WM25 | WM25/20 | WALLMATE NYLON MP20 | 20 | 24 | 10 | 33 | 15 |
| | R467515 | WALLMATES NYLON CD10 | 10 | 24 | 10 | 33 | 15 |
| | R463579 | WALLMATES+SCREWS NYLON CD4 * | 4 | 24 | 10 | 33 | 15 |
| | R463548 | WALLMATES+SCREWS+HOOKS CD4 ** | 4 | 24 | 10 | 33 | 15 |
| | WMZ | WALLMATE ZINC BX100 | 100 | 24 | 10 | 33 | 15 |
| WMZ | WMZ/20 | WALLMATE ZINC MP20 | 20 | 24 | 10 | 33 | 15 |
| | R463517 | WALLMATES W/SCREWS ZINC CD4 * | 4 | 24 | 10 | 33 | 15 |

^{*} includes one 8g screw per anchor

For further information, please contact Ramset*

AU - PHONE: 1300 780 063 www.ramset.com.au NZ - PHONE: 1800 RAMSET (726738) www.ramset.co.nz

^{**} includes one 8g screw and 1 hook per anchor